



# CINDY JEAN LAB

## 260' DP-2

### SAFE, DEPENDABLE, AND MODERN OFFSHORE SUPPORT

#### REGISTRATION

USCG Official Number	1193583
GRT / ITC	2,183
Net	654
IMO	9421398
Classification ID	08178247
Classification	ABS
Year Built	2008
Flag	USA
Builder	Gulf Island Shipyards
O.N.	1193583
Certifications	Subchapters L&I, SOLAS, and ACP
Notations	✘A1, ✘AMS, ✘DPS-2

#### MAIN CHARACTERISTICS

Length overall	251 ft	(76.6 m)
Beam	56 ft	(17.1 m)
Depth	19.5 ft	(5.9 m)
Max Draft	16.6 ft	(5 m)
Min Draft	5.9 ft	(2.3 m)

#### PERFORMANCE

Max Speed	12 knots	240 gal/hr	(908.5 l/hr)
Cruising Speed	11 knots	140 gal/hr	(529.9 l/hr)
DP		37 gal/hr	(140 l/hr)

#### MACHINERY

Main Engines	2x Caterpillar 3516B
Total Horsepower	5,150 BHP
Main Propulsion	2 x Azimuthing Z- Drives
Total Horsepower	5,150 BHP
Main Generators	3 x Caterpillar C-18
Total Rating	1,020 kW
Bow Thrusters	2 x Caterpillar 3508B
Total Horsepower	2,100 BHP
Emergency Generator	Catepillar C9 175W

#### CAPACITIES AND DISCHARGE RATES

Deadweight	3,100 Lt	(3,370 Mt)
Deck Strength	1,024 lbs/ft <sup>2</sup>	(5 t/m <sup>2</sup> )
Cargo Deck Area	176 ft x 48 ft	(8,848 ft <sup>2</sup> )
	53.6 M X 14.6 M	(783 M <sup>2</sup> )
Drill/Rig Water	277,680 USG	(1003 M <sup>3</sup> )
Fuel	186,200 USG	(705 M <sup>3</sup> )
Liquid Mud	9,566 Bbls	(1,545 M <sup>3</sup> )
(Multiple Tank Configurations with Segregated Fills and Discharges)		
Dry Bulk (8) Tanks	6,600 ft <sup>3</sup>	(187 M <sup>3</sup> )
Potable Water	38,400 USG	(125 M <sup>3</sup> )

#### ELECTRONICS

- (2) Kongsberg K-POS DP-2 Systems Full Auto With Full and Mixed Joy Stick Mode C-Joy, C-Wing, Alarm Printer, Multi Targets
- (2) DGPS Receivers
- (1) Radius 1000 Interrogator
- (2) 700 Transponders
- (1) MK4.2 2000m.Fan Beam
- (2) gyro compasses
- (2) wind sensors
- (2) MRU
- (2) Radars
- GMDSS
- (4) VHF Radios
- (2) SSB Radios
- Bridge Navigation Watch Alarm System

#### ACCOMMODATIONS

Max Capacity	32 People
(2) 1 Person rooms	
(5) 2 Person rooms	
(5) 4 Person rooms	

#### SPECIAL FEATURES

- Computerized Vessel Stability Management
- Online and Satellite Communications
- Certified Standby Endorsement (120 Persons)

Discharge Rate	650 GPM	(148 M <sup>3</sup> /hr)
Discharge Rate	650 GPM	(148 M <sup>3</sup> /hr)
Discharge Rate	700 GPM	(159 M <sup>3</sup> /hr)
Discharge Rate	1,000 ft <sup>3</sup> /hr	(43 M <sup>3</sup> /hr) 80psi

CINDY JEAN LAB

**NOTICE:** The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

# CINDY JEAN LAB

